



SMT-3215

32" LED monitor



Key Features

- 32 inch FHD Monitor, support up to 1920×1080 @60Hz
- Brightness 300 cd/m² (Typical), Contrast 3200:1 (Minimum) 4000:1 (Typical)
- Viewing Angle (H/V) : 178°/178°, Response Time : 20ms (Typical)
- Video Input : HDMI, DP, VGA
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-3215

32" LED monitor



Specifications

Display	
Type	LED Monitor
Screen Size	31.5"
Max. Resolution	1920*1080 60Hz (FHD)
Brightness	300 cd/m ² (Typ)
Contrast Ratio	3200:1 (Min) 4000:1 (Typ)
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7M
Response Time	20ms(Typ)
Panel Life	30,000 hours

Interface		
Video	Connectors	VGA (1) HDMI 1.4(1), DP 1.2(1) Audio-in(1) Audio-out (1)
VGA	Connector	1port Analog D-sub(15 pin)
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
HDMI	Connector	HDMI
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
DP	Connector	DP
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
Audio	Connector	Audio in/out
	Output Signal	Loop-through line level(PC only), Speakers : 4Ω 2.5Wx 2

On Screen Display	
Functions	VESA™ DPM Compatible
Language	Korean, English, Русский, Deutsch, Français, Español, Italiano, Português, Chinese (Simplified), Chinese (Traditional), Japanese, Arabic

General

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com.

Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	<60W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions with Stand (WxHxD)	714.0*484.2*200.8mm
	Dimensions without Stand (WxHxD)	714.0*423.7*53.7mm
	Weight	7.28kg(with stand), 5.9Kg(without stand)
	Cabinet Color	Black
	VESA Mounts Interface	100 x 100mm