



Network

Dome

# XNV-A8084R

5MP AI IR Vandal Dome Camera



## Key Features

- 3.3~9.3mm (2.8x) motorized varifocal
- Dual NPU for AI-based Image enhancement
- Analytics events based on AI engine :  
Object detection (Person/Face/Vehicle/License plate),  
IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion),  
Slip&Fall detection, Face mask detection,  
Social distancing detection, Motion detection
- Business intelligence based on AI engine :  
People/Vehicle/Crowd counting, Queue management, Heatmap
- Support BestShot and full attributes
- Support Dynamic Privacy Masking
- extremeWDR, WiseNR II (Based on AI engine),  
WiseStream(Based on AI engine)
- WiseIR: IR viewable length 40 m (131.23 ft)
- IP66, IP67, NEMA4X, IK10
- NEMA TS-2 (2.2.7.2-8, 2.2.8, 2.2.9)
- Support Wisepower(Power monitoring, ECO mode)
- Use recycled plastic
- Device certificate(Hanwha Vision Root CA),  
Secure storage  
(Secure element with FIPS 140-3 level3/CC EAL6+ certified), SBOM

# XNV-A8084R

5MP AI IR Vandal Dome Camera



## Specifications

### Video

Imaging Device	1/2.8" CMOS
Resolution	2560x1920, 2560x1440, 1920x1080, 1600x1200, 1280x960, 1280x720, 1024x768, 800x600, 640x480, 640x360, 320x240, 320x180
Max. Framerate	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps(@5MP Max. 5fps)
Min. Illumination	Color: 0.04Lux(F1.3, 1/30sec, 30IRE) BW: 0.004Lux(F1.3, 1/30sec, 30IRE), 0Lux(IR LED on)
Video Out	USB: Micro USB Type C for installation

### Lens

Focal Length (Zoom Ratio)	3.3~9.3mm(2.8x) motorized varifocal
Max. Aperture Ratio	F1.3(Wide)~F2.3(Tele)
Angular Field of View	H: 99°(Wide)~31°(Tele) V: 71°(Wide)~23°(Tele) D: 133°(Wide)~39°(Tele)
Min. Object Distance	0.5m(1.64ft)
Focus Control	Simple focus, manual
Lens Type	P-iris(IR corrected)

### Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	0°~360° / 0°~75° / 0°~355°
---------------------------	----------------------------

### Operational

Camera Title	Displayed up to 85 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SSDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR V, WiseNR II (Based on AI engine)
Digital Image Stabilization	Support
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Privacy Masking	32ea, 8point polygonal zones - Color: gray/green/red/blue/black/white/purple/yellow - Mosaic Dynamic Privacy Mask(Based on AI engine) - Color: gray/green/red/blue/black/white/purple/yellow - Mosaic
Gain Control	Off / Max Gain / Manual
White Balance	ATW / NarrowATW / AWC / Manual / Indoor / Outdoor
LDC	Support(Fill/Stretch mode)
Electronic Shutter Speed	Minimum / Maximum / Anti flicker(2~1/30,000sec) Prefer shutter control(Based on AI engine)

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com).

Hanwha Vision is formerly known as Hanwha Techwin.

Video Rotation	Flip, mirror, hallway view(90°/270°)
Analytics	<p>Classified object type: Person/Face/Vehicle(Type: car/bus/truck/motorcycle/bicycle)/License plate            Attributes: Person(Gender, Clothing top/bottom color, Bag), Face(Age, Gender, Mask, Glasses),            Vehicle(Type: car/bus/truck/motorcycle/bicycle, Color)            Support BestShot</p> <p>Analytics events based on AI engine            - Motion detection, Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit/Appear/Disappear), Slip &amp; fall detection, Face mask detection, Social distancing detection</p> <p>Analytics events            - Defocus detection, Tampering, Shock detection, Audio detection</p>
Business Intelligence	Based on AI engine: People/Vehicle/Crowd counting, Queue management, Heatmap
Alarm I/O	2 configurable I/O ports *Support extra alarm I/O via optional I/O box
Alarm Triggers	Analytics, Network disconnection, Alarm input, Time schedule, MQTT subscription, Day/Night, Storage disruption
Alarm Events	<p>When alarm trigger occurred</p> <ul style="list-style-type: none"> <li>- File upload(image): e-mail/FTP/SFTP</li> <li>- File upload(video clip): FTP/SFTP</li> <li>- Notification: e-mail</li> <li>- Recording: SD/SDHC/SDXC or NAS recording at event triggers</li> <li>- Alarm output</li> <li>- Handover: PTZ preset, send message by HTTP/HTTPS/TCP</li> <li>- Audio clip playback(WAV, MP3)</li> <li>- MQTT: publication</li> </ul>
Audio In	Selectable(mic in/line in)
Audio Out	Line out
Light Type	IR LED
Light Viewable Length	WiseIR 40m(131.23ft)
IR Wavelength	850nm
<b>Network</b>	
Ethernet	Metal shielded RJ-45(10/100BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High MJPEG
Audio Compression	G.711(PCM): 8kHz(64Kbps) G.726(ADPCM): 8kHz(16/24/32/40Kbps) AAC-LC: 16kHz(48Kbps) OPUS: 48kHz(64Kbps)
Smart Codec	WiseStream(Based on AI engine)
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 5 profiles, 3 virtual channel support)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP/SFTP, SMTP(StartTLS), ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), CDP, MQTT, Syslog
Application Programming Interface	ONVIF Profile S/G/T/M SUNAPI(HTTP API) Hanwha Vision Open Platform
<b>Security</b>	
OS / Firmware Protect	Encrypted Firmware, Secure boot, Signed Firmware
User authentication	Digest Authentication, Prevent brute-force attack
Network authentication	802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2)
Secure Communication	HTTPS, SRTP, WSS(Websocket secure)
Access Control	IP-based access control, MAC-based access control, Auto logout
Data Protect	Encryption Credentials, Encrypt compress for live recording file export

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com).

Hanwha Vision is formerly known as Hanwha Techwin.

Audit	Access / System / Event Log management
Device ID	Device Certificate(Hanwha vision Root CA)
Secure Storage	Secure element, SDcard partition encrypt
Security Certificate	ETSI EN 303 645, Secure element(FIPS 140-3 level3, CC EAL6+)

#### General

Webpage Language	English, Korean, Simplified Chinese, Traditional Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Edge Storage	Micro SD/SDHC/SDXC 1slot 1TB
Memory	4GB RAM, 8GB eMMC

#### Environmental & Electrical

Operating Temperature / Humidity	-40°C~+50°C(-40°F~+122°F) +74°C(+165°F)(MAX) based on NEMA-TS 2(2.2.7) * Start up should be done at above -30°C 0~100%RH(Condensing) Humidity control with AIR vent
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / 0~90% RH
EPA(Effective Projected Area)	0.02m <sup>2</sup>
Certification	IP66/IP67, NEMA4X, IK10, NEMA-TS 2(2.2.7.2-8, 2.2.8, 2.2.9)
Input Voltage	PoE(IEEE802.3af, Class3)
Power Consumption	PoE: Max. 9.4W, typical 7.0W Support Wisepower - Power monitoring(Max./Current/Avg.) - ECO mode

#### Mechanical

Color / Material	White / Aluminum Bubble: Hard-coated dome Recycled plastic: 4.52%
RAL Code	RAL9003
Product Dimensions / Weight	ø160x118mm(6.30x4.65"), 1,210g(2.67lb)
Compatible Conduit hole / Gangbox	12.7mm(1/2")(M20) Single, double, 4" octagon, 4" square

#### Certifications & Standards

EMC	FCC 47 CFR 15 Subpart B Class A ICES-3(A)/NMB-3(A) CE/UKCA - EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3 VCCI CISPR 32 Class A RCM AS/NZS CISPR 32 Class A KS C 9832 Class A, KS C 9835
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1 IEC/EN 62471
Environment	IEC/EN 63000 IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA-TS 2(2.2.7.2-8, 2.2.8, 2.2.9) IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78

#### Compatible Models

Hanging Adaptor	SBP-160HWMW1
Back Box	SBV-180BW, SBV-180WW
Ceiling Mount (Assy)	SBP-150CMI, SBP-300CMI, SBP-300CMW1, SBP-900CMW, SBP-300CMTW, SBP-300CMTS
Ceiling Mount (Single Unit)	SBP-180CMB, SBP-140CMB, SBP-180CMS, SBP-900CMP, SBP-300CMP, SBP-150CMP, SBP-C15P, SBP-C15H
Wall Mount	SBP-160WMW1, SBP-400WMW, SBP-250WMW, SBP-300WMW, SBP-300WMW1
Pole Mount	SBD-180PMW, SBP-300PMW2

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com).

Hanwha Vision is formerly known as Hanwha Techwin.

In-ceiling Mount	SHD-1600FPW, SHD-1600FW
Corner Mount	SBP-156KMW, SBP-300KMW1
Parapet Mount	SBP-156LMW1, SBP-300LMW
Tilt Mount	SBP-160TMW1
Cabinet	SBP-150NBW, SBP-300NBW
Weather Cap	SBV-161WCW
Interface Box	SPM-4210
Other Compatible Models	SPP-C7400, SPB-VAN88W, SBP-115PFA

---

DORI (EN62676-4 standard)	
Detect (25PPM/ 8PPF)	Wide: 43.7m(143.47ft) / Tele: 184.6m(605.71ft)
Observe (63PPM/ 19PPF)	Wide: 17.5m(57.39ft) / Tele: 73.8m(242.29ft)
Recognize (125PPM/ 38PPF)	Wide: 8.7m(28.69ft) / Tele: 36.9m(121.14ft)
Identify (250PPM/ 76PPF)	Wide: 4.4m(14.35ft) / Tele: 18.5m(60.57ft)

---