



Network

Dome

TNV-C8014RM

T AI 5MP IR Mobile Camera



Key Features

- Max. 5MP resolution
- 3.0 mm fixed lens
- Color: 0.03Lux(F1.6, 1/30sec), BW: 0.003Lux(F1.6, 1/30sec, 30IRE)
- Maximum 30fps@5MP (H.265/H.264)
- IR viewable length 30m (98.42ft)
- Hard-coated dome bubble,
- EIS, Shock detection, Heater, Built-in Mic
- H.265, H.264, MJPEG, WiseStreamIII (Using AI engine)
- Analytics events based on AI engine (NPU)
- EN50155 compliance
- IP66, IK10
- PoE: Max 7.2W, M12 connector

TNV-C8014RM

T AI 5MP IR Mobile Camera



Specifications

| Video | | |
|-------------------------------|-----------------------|--|
| Imaging Device | Size | 1/2.8" |
| | Type | CMOS |
| Resolution | | 2592x1944, 2560x1440, 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |
| Max. Framerate | H.265/H.264 | 30fps/25fps(60Hz/50Hz) |
| | MJPEG | 30fps(@5MP Max. 5fps) |
| Min. Illumination (Lux) | Color(1/30sec, 30IRE) | 0.03 |
| | BW(1/30sec, 30IRE) | 0.003 |
| Video Out | | USB: Micro USB Type B |
| Lens | | |
| Focal Length (mm) | | 3.0 |
| Max Aperture Ratio (F number) | Wide | 1.6 |
| Angular Field of View | Horizontal | 100° |
| | Vertical | 73° |
| | Diagonal | 129° |
| Min. Object Distance | | 0.5m(1.64ft) |
| Focus Control | | Fixed |
| Lens Type | | Fixed iris |
| Mount Type | | M12 |
| Pan / Tilt / Rotate | | |
| Pan / Tilt / Rotate Range | Pan | ±5° |
| | Tilt | 0°~67° |
| | Rotate | ±90° |
| Operational | | |
| Day & Night | | Auto(ICR) |
| Backlight Compensation | | BLC, WDR, SSDR, ClearHDR |
| Wide Dynamic Range (dB) | | 120 |

Operational

| | | |
|--|----------------|---|
| Digital Noise Reduction | | WiseNR II (Based on AI engine), SSNR V |
| Motion Detection | Quantity | 8ea |
| | Shape | 8point Polygonal zones |
| Privacy Masking | Quantity | 32ea |
| | Shape | 4point Quadrangle zones |
| | Color / Option | Gray, Green, Red, Blue, Black, White |
| Gain Control | | Low, Middle, High |
| White Balance | | ATW, AWC, Manual, Indoor, Outdoor |
| LDC | | Support |
| Electronic Shutter | Mode | Minimum, Maximum, Anti flicker, Prefer shutter control(Based on AI engine) |
| | Speed Range | 1/5~1/25,000sec |
| Video Rotation | | Flip, Mirror, Hallway view(90°/270°) |
| Alarm Triggers | | Analytics, Network disconnect, MQTT subscription |
| Alarm Events When Alarm Trigger Occurred | | File upload(image): e-mail/FTP/SFTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Handover: PTZ preset,send message by HTTP/HTTPS/TCP,Audio clip playback, MQTT: publication |
| Audio In | | Selectable(mic in/line in), Built-in mic |
| Audio Out | | Line out |
| Light Type | | IR LED |
| Light Viewable Length | IR | 30m(98.42ft) |
| IR Wavelength | | 850nm |

Analytics

| | | |
|------------------------|--------------------|--|
| Classified Object Type | | Person, Vehicle |
| Attributes | Person | Upper/Lower clothes color |
| | Vehicle | Type(car, bus, truck, motorcycle, bicycle), Color |
| Thumbnail | | BestShot |
| Analytics Events | Based on AI Engine | Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit), Motion detection |
| | Normal | Defocus detection, Tampering, Shock detection, Virtual area(Appear/Disappear) |
| Business Intelligence | Based on AI Engine | People counting, Queue management, Heatmap, Vehicle counting |

Network

| | | |
|-------------------|--|---|
| Ethernet | | M12 |
| Video Compression | | H.265/H.264: Main/High, MJPEG |
| Audio Compression | | G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 48kbps at 16kHz |

Network

| | | |
|-----------------------------------|--------------------|---|
| Smart Codec | | Manual, WiseStreamIII |
| Bitrate Control | | H.265/H.264: CBR or VBR, MJPEG: VBR |
| Streaming | Unicast | Up to 20 users |
| | Multicast | Support |
| | Multiple Streaming | Up to 5 profiles |
| Protocol | | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SFTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT |
| Application Programming Interface | ONVIF | S, G, T, M |
| | Others | SUNAPI(HTTP API), Hanwha Vision Open Platform |
| Direct Cloud Connection | | Support |

Security

| | | |
|------------------------|--|---|
| OS / Firmware Protect | | Encrypted firmware, Secure boot, Signed firmware |
| User authentication | | Digest authentication, Prevent brute-force attack |
| Network authentication | | IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2) |
| Secure Communication | | HTTPS, WSS(WebSocket Secure) |
| Access Control | | IP-based access control |
| Data Protect | | Encryption credentials, Encrypt compress for live recording file export |
| Audit | | Access / System / Event Log management |
| Device ID | | Device certificate(Hanwha Vision Root CA) |
| Secure Storage | | SDcard partition encrypt(AES-256) |

General

| | | |
|--------------|--------------------|--------------------|
| Memory | RAM | 2GB |
| | Flash | 1GB |
| Edge Storage | Micro SD/SDHC/SDXC | Max. 256GB x 1slot |

Environmental & Electrical

| | | |
|---------------------|-------------|--|
| Operating Condition | Temperature | -40°C~+55°C(-40°F~+131°F) |
| | Humidity | 0~100% RH(condensing) |
| | Others | Start up should be done at above -30°C, Humidity control with AIR vent |
| Storage Condition | Temperature | -40°C~+55°C(-40°F~+131°F) |
| | Humidity | 0~95% RH(non-condensing) |
| Input Voltage | | PoE(IEEE802.3af, Class3) |
| Power Consumption | PoE | Max. 7.2W, typical 4.2W |

Mechanical

| | |
|-------|-------|
| Color | White |
|-------|-------|

Mechanical

| | |
|--------------------|--------------------------------|
| Material | Aluminum, Hard-coated dome |
| RAL Code | RAL9003 |
| Product Dimensions | 106x105x55mm(4.17x.4.13x2.17") |
| Product Weight | 466g(1.03 lb) |

Certifications & Standards

| | |
|-------------|--|
| EMC | EN 50121-4, FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS-NZS CISPR 32 Class A, EN 50121-3-2 |
| Safety | UL 62368-1, CAN/CSA C22.2 NO. 62368-1, IEC 62471 |
| Environment | IEC/EN 63000, IEC 60529 IP66, IEC 62262 IK10, EN 50155, IEC 62236-4, EN 50121-4, JIS E 4031, EN 50498, IEC/EN 61373, EN 45545, JIS E 5006, IEC 62236-3-2 |

DORI (EN62676-4 standard)

| | | |
|---------------------------|------|-----------------|
| Detect (25PPM/ 8PPF) | Wide | 43.5m(142.71ft) |
| Observe (63PPM/ 19PPF) | Wide | 17.5m(57.09ft) |
| Recognize (125PPM/ 38PPF) | Wide | 8.7m(28.54ft) |
| Identify (250PPM/ 76PPF) | Wide | 4.3m(14.27ft) |

TNV-C8014RM
T AI 5MP IR Mobile Camera



CAD

Unit: mm [inch]

