

DH-PFM3350-2000L

European Standard 230V - Line-interactive 2000VA/1200W Uninterruptible Power Supply



Series Overview

The Uninterruptible Power Supply performs outstandingly, offering highly stable output. It easily adapts to complex environments, such as mains power grids, and has protection against overvoltage and overload. Designed for convenience, it is plug and play, and easy to use.

Scene

For indoor use, the temperature range is 0°C to 40°C, with ambient humidity not exceeding 90%, and no condensation allowed.

Technical Specification

Capacity

Capacity	2000 VA, 1200 W
----------	-----------------

Input

Input Voltage	170–280 VAC
---------------	-------------

Input Current	9.5 A
---------------	-------

Rated Input Frequency	50/60 Hz
-----------------------	----------

Power Factor	≥0.6
--------------	------

Output

Output Voltage	230 VAC
----------------	---------

Output Current	9.2 A
----------------	-------

Output Power	2000 VA, 1200 W
--------------	-----------------

Output Frequency	50/60Hz
------------------	---------

Switch Time	Typical 4 ms–8 ms
-------------	-------------------

Output Wave	AC Mode: Pure sine wave; Battery Mode: Simulated sine wave
-------------	---

- Comes with a wide voltage input range of 170–280 VAC, and easily adapts to fluctuations and various grid environments.
- Operates quietly for a serene environment.
- Offers digital voltage stabilization and automatically adjusts the voltage.
- Fast charging in just 4 hours.
- Rapid switching of 4-8 milliseconds.
- Protects against overload, short circuit, overcharging, and over-discharge.

Battery

Built-in Battery	Yes
Battery Type	Lead-acid battery
Qty.of Battery	2 × 9 Ah
Charging Current	1 A
Limited Charge Voltage	13.7 V/pcs
Charging Time	4–6H to 90%
Max Travel Time on Full Battery	3 min

Screen

Screen Status	AC Mode: Displays both INPUT and OUTPUT as 230 VAC; Battery Mode: Displays INPUT as 0 VAC; displays OUTPUT as 230 VAC; Fault Mode: Displays as 0
---------------	--

Alarm

Alarm Indicator	Battery Mode: Beeps once every 10 seconds; Low Battery: Beeps once every second; Overload: Beeps once every 0.5 seconds; Battery Replacement: Beeps once every 2 seconds; Fault: Beeps continuously
-----------------	---

Protection

Types of Protection	Protects against overload, battery overcharge, and over-discharge
Overload Capacity	AC Mode Overload: 110% + 20% / – 10%. The UPS shuts down after 5 minutes and reports an overload fault; AC Mode Overload: 120% + 20% / – 10%. The UPS shuts down immediately and reports an overload fault; Battery Mode Overload: 120% + 20% / – 10%. The UPS shuts down immediately and reports an overload fault

Plugs and Sockets

Input Plug	European standard
Input Cable Length	1.2 m (3.94 ft)
Socket Standard	European standard

Uninterruptible Power Supply | DH-PFM3350-2000L

Number of Output Sockets	4
--------------------------	---

Other

Built-in Fan	Yes
--------------	-----

Structure

Product Dimensions	374.5 mm × 138.4 mm × 166.5 mm (14.74" × 5.45" × 6.56") (L × W × H)
Packaging Dimensions	470 mm × 195 mm × 255 mm (18.50" × 7.68" × 10.04") (L × W × H)
Casing Material	Plastic front cover + metal body
Appearance Color	Black
Net Weight	12.2 kg (26.90 lb)
Gross Weight	12.6 kg (27.78 lb)

Environment

Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Operating Humidity	0%–90%, non-condensing
Storage Temperature	–15 °C to +55 °C (+5 °F to +131 °F)
Storage Humidity	0%–90%, non-condensing

Certifications

Certifications	CE LVD: EN IEC 62040-1: 2019+A11: 2021; CE EMC: EN 62040-2: 2006; EN IEC 62040-2: 2018; EN IEC 61000-3-2: 2019+A1: 2021+A2: 2024; EN 61000-3-3: 2013+A1: 2019+A2: 2021
----------------	---

Ordering Information

Type	Model	Description
Uninterruptible Power Supply (with battery)	DH-PFM3350-2000L	European Standard 230V - Line-interactive 2000VA/ 1200W Uninterruptible Power Supply

Dimensions (mm[inch])

