

DH-HAC-HFW2802TU-A

4K Starlight HDCVI Fixed-focal Bullet Camera



System Overview

The Pro Series contains a series of highly reliable and flexible cameras, making it a great choice for SMB solutions and projects. It has Starlight technology, up to 130 dB true WDR and 3DNR, and produces vivid images in rich detail even under difficult lighting conditions.

Functions

Starlight

With its large image sensor and large aperture, the camera delivers high performance and quality, even in low-light conditions. The starlight feature allows the camera to capture highly detailed images in accurate color, recognizing targets even at night or in scenes with limited light.

Wide Dynamic Range

With its advanced Wide Dynamic Range technology (WDR), the camera captures highly detailed images and produces high-definition recordings in high-contrast lighting conditions, and in scenes with backlighting or shadows.

Broadcast-quality Audio

Audio signal transmission over coaxial cables is supported by the HDCVI camera. It adopts a unique audio processing and transmission technology that restores source audio and eliminates noise, ensuring the quality and reliability of the audio information that is collected. This becomes important for video surveillance applications that use audio information as a type of supplementary evidence.

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals (video, audio*, data and power) which are simultaneously transmitted over a coaxial cable. Dual-way data transmission allows the HDCVI camera to interact with the XVR to perform various actions such as sending control signals and triggering alarms. HDCVI technology also supports PoC, which makes the camera easy and quick to install.

* Audio input is available for select HDCVI camera models.

* The parameters and datasheets below can only be applied to 2802-S2 series.

- Max. 15 fps@4K.
- Starlight, 120 dB true WDR, 3D NR.
- Smart IR Illumination.
- 80 m illumination distance.
- Super Adapt.
- Built-in MIC.
- 3.6 mm fixed lens (6 mm optional).
- CVI/CVBS/AHD/TVI switchable.
- IP67, 12 VDC.



Long Distance Transmission

HDCVI technology provides long distance transmission in real time without transmission loss. It supports transmission distances up to 700 m for 2-MP/5-MP/8-MP HD videos through coaxial cables, and up to 300 m through UTP cables. The results were obtained and verified through rigorous testing in Dahua's test laboratory.

Super Adapt

With its intelligent algorithm, the camera automatically adjusts its parameters to provide optimal performance and vivid images.

Advanced 3DNR

Dahua's advanced 3DNR technology reduces image noise with little to no impact on image sharpness, especially in poor lighting conditions. It detects the noise, and compares the sequential frames to effectively reduce the noise. It also makes efficient use of bandwidth, saving on storage space.

Smart IR Illumination


With its IR illumination, the camera provides optimal performance in low light conditions, ensuring uniformity in the brightness of B/W images. Through its smart IR technology, the camera also compensates for the distance of targets by adjusting the intensity of its IR LEDs, preventing overexposure of images as targets move closer to the camera.

Protection (IP67, Wide Voltage)


IP67: The camera passed a series of rigorous dust and immersion tests. Its enclosure is both dust-proof and waterproof, and can function normally while being immersed in 1 m deep water for up to 30 minutes.
Wide voltage: The camera has $\pm 30\%$ input voltage tolerance (for some power supplies) and a wide voltage range, making it suitable for a variety of outdoor scenarios.

Technical Specification						White Balance		Auto;Area white balance			
Camera								Gain Control		Auto/Manual	
Image Sensor		4K CMOS						Noise Reduction		3D NR	
Max. Resolution		3840 (H) × 2160 (V)						Illumination Mode		Smart IR	
Scanning System		Progressive						Defog		Electronic defog	
Electronic Shutter Speed		PAL: 1/3 s–1/100000 s NTSC: 1/4 s–1/100000 s						Digital Zoom		4×	
Min. Illumination		0.001 lux@F1.5 (Color, 30 IRE) 0.0001 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on)						Mirror		Yes	
S/N Ratio		>65 dB						Privacy Masking		Off/On (8 areas, rectangle)	
Illumination Distance								Certification			
Illuminator On/Off Control		Auto						Certifications		CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 15, Subpart B; UL: UL62368-1 + CAN/CSA C22.2 No. 62368-1-14	
Illuminator Number		4 (IR light)						Port			
Pan/Tilt/Rotation Range		Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°						Video Output		Video output choices of CVI/TVI/AHD/CVBS by one BNC port (DIP Switch)	
								Audio Input		One channel built-in MIC	
Lens								Power			
Lens Type		Fixed-focal						Power Supply		12 VDC ± 30% (It is recommended to use a power adapter to supply the power for one camera)	
Auto Focus		No						Power Consumption		Max 9.6 W (12 VDC, IR on)	
Lens Mount		M12						Environment			
Focal Length		3.6 mm; 6 mm						Operating Temperature		–40 °C to +60 °C (–40 °F to +140 °F)	
Max. Aperture		F1.5						Operating Humidity		<95% (RH), non-condensing	
Field of View		3.6 mm: H: 87°; V: 49°; D: 99° 6 mm: H: 60°; V: 35°; D: 68°						Storage Temperature		–40 °C to +60 °C (–40 °F to +140 °F)	
Iris Control		Fixed						Storage Humidity		<95% (RH), non-condensing	
Close Focus Distance		3.6 mm: 2.2 m (7.22 f) 6 mm: 4.0 m (13.12 f)						Protection		IP67	
DORI Distance	Lens	Detect	Observe	Recognize	Identify		Structure				
	3.6 mm	98.0 m (321.52 ft)	39.2 m (128.61 ft)	19.6 m (64.30 ft)	9.8 m (32.15 ft)		Casing Material		Metal		
	6 mm	140.0 m (459.32 ft)	56.0 m (183.73 ft)	28.0 m (91.86 ft)	14.0 m (45.93 ft)		Product Dimensions		244.1 mm × 90.4 mm × 90.4 mm (9.61" × 3.56" × 3.56")		
	*DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool.						Net Weight		0.76 kg (1.68 lb)		
								Gross Weight		1.00 kg (2.20 lb)	
								Installation		Wall mount; ceiling mount; vertical pole mount	
Video											
Video Frame Rate		CVI: PAL: 4K@15 fps;5M@25 fps; 4M@25 fps NTSC: 4K@15 fps;5M@25 fps; 4M@30 fps AHD: PAL: 4K@15 fps; NTSC: 4K@15 fps TVI: PAL: 4K@15 fps; NTSC: 4K@15 fps CVBS: PAL: 960H; NTSC: 960H									
Resolution		4K (3840 × 2160); 5M (2880 × 1620); 4M (2560 × 1440); 960H (960 × 576/960 × 480)									
Day/Night		Auto(ICR)/Color/B/W									
BLC		BLC; HLC; WDR; HLC-Pro									
WDR		120 dB									

Ordering Information		
Type	Model	Description
2M Camera	DH-HAC-HFW2802TUP-A	4K Starlight HDCVI Fixed-focal Bullet Camera,PAL
	DH-HAC-HFW2802TUN-A	4K Starlight HDCVI Fixed-focal Bullet Camera,NTSC
Accessories (Optional)	PFA130-E	Water-proof Junction Box
	PFA152-E	Pole Mount Bracket
	PFM800-4K	1-CH Passive Video Balun
	PFM321D	12V 1A Power Adapter
	PFM904	Integrated Mount Tester



Dimensions (mm [inch])



Accessories

Optional:



PFA130-E
Water-proof
Junction Box



PFA152-E
Pole Mount
Bracket



PFM800-4K
1-CH Passive Video
Balun



PFM321D
12V 1A Power
Adapter



PFM904
Integrated Mount
Tester