



# SHB-4200H

Indoor Housing for Fixed Camera



## Key Features

- For fixed lens application
- Rugged and compact all aluminum construction
- Wall/ceiling installations
- Easy to install slide open type
- Built in bracket

# SHB-4200H

## Indoor Housing for Fixed Camera

### Specifications

#### Environmental

|                                  |   |
|----------------------------------|---|
| Operating Temperature / Humidity | -35°C ~ +50°C (-31°F ~ +122°F)<br>/ Less than 90% RH        |
| Fan/Heater                       | Support<br>(Heater : 4°C ± 3°C on / Blower : 45°C ± 5°C on) |
| Certification                    | IP66  |

#### Electrical

|                   |  |
|-------------------|--|
| Input Voltage     | 24VAC  |
| Power Consumption | 21.6W<br>AC FAN(1.6W) : 1.6W * 1EA<br>AC HEATER(20W) : 20W * 1EA |

#### Mechanical

|                             |  |
|-----------------------------|--|
| Color                       | Ivory  |
| Material                    | Aluminum   |
| Product dimensions / weight | Outside : 148(W)x107(H)x421(D)mm<br>Inside : 84(W)x78(H)x260(D)mm  |
| Pan / Tilt / Rotate Range   | 0°~360° / 0°~90°   |
| Supported products          | Box cameras (Network/Analog)<br>※ For further compatible models, please visit our website or use Toolbox |