



Network

BOX

# XNB-6001

Remote Head Cam & Lens modules



## Key Features

- Max. 2Megapixel (1920 x 1080) resolution
- H.265, H.264, MJPEG codec support, Multiple streaming
- Max. 60fps@2MP (H.265 / H.264)
- WDR (120dB), Defog, DIS, WiseStreamII
- Tampering, Loitering, Directional detection, Fog detection
- Audio detection, Digital auto tracking, Heatmap
- Queue management, Face detection, People counting
- Motion detection, Handover
- Memory slot (Max. 256GB), Hallway View
- LDC, PoE / 12V DC, Bi-directional audio support

# XNB-6001

Remote Head Cam & Lens modules



## Specifications

### Video

<b>Resolution</b>	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
<b>Max. Framerate</b>	H.265/H.264: Max. 60fps/50fps(60Hz/50Hz) MJPEG: Max. 30fps/25fps(60Hz/50Hz)
<b>Video Out</b>	CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation USB: Micro USB Type B, 1280x720 for installation

### Lens

<b>Optional Lens</b>	SLA-T1080F, SLA-T2480, SLA-T2480V, SLA-T4680, SLA-T4680V
----------------------	--

### Operational

<b>Camera Title</b>	Displayed up to 85 characters
<b>Day &amp; Night</b>	Auto(Electrical)
<b>Backlight Compensation</b>	BLC, HLC, WDR, SSSDR
<b>Wide Dynamic Range</b>	120dB
<b>Digital Noise Reduction</b>	SSNR V
<b>Digital Image Stabilization</b>	Support
<b>Defog</b>	Support
<b>Motion Detection</b>	8ea, 8point polygonal zones
<b>Privacy Masking</b>	32ea, 4 point polygonal zones - Color: Grey/Green/Red/Blue/Black/White - Mosaic
<b>Gain Control</b>	Low / Middle / High
<b>White Balance</b>	ATW / AWC / Manual / Indoor / Outdoor
<b>LDC</b>	Support
<b>Electronic Shutter Speed</b>	Minimum / Maximum / Anti flicker (2~1/12,000sec)
<b>Video Rotation</b>	Flip, Mirror, Hallway view(90/270)
<b>Analytics</b>	Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Digital auto tracking, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line
<b>Alarm I/O</b>	Input 1ea / Output 1ea
<b>Alarm Triggers</b>	Analytics, Network disconnect, Alarm input
<b>Alarm Events</b>	File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC or NAS recording at event triggers Alarm output DPTZ preset
<b>Audio In</b>	Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm
<b>Audio Out</b>	Line out, Max.output level: 1Vrms

### Network

<b>Ethernet</b>	RJ-45(10/100BASE-T)
<b>Video Compression</b>	H.265/H.264: Main/Baseline/High, MJPEG
<b>Audio Compression</b>	G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz
<b>Smart Codec</b>	Manual(5ea area), WiseStream II

<b>Bitrate Control</b>	H.264/H.265: CBR or VBR MJPEG: VBR
<b>Streaming</b>	Unicast(20 users) / Multicast Multiple streaming (Up to 10 profiles)
<b>Protocol</b>	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTSP
<b>Security</b>	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP)
<b>Application Programming Interface</b>	ONVIF Profile S/G/T SUNAPI(HTTP API) Wisenet open platform

## General

<b>Webpage Language</b>	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
<b>Edge Storage</b>	Micro SD/SDHC/SDXC 1slot 256GB
<b>Memory</b>	1024MB RAM, 256MB Flash

## Environmental & Electrical

<b>Operating Temperature / Humidity</b>	-10°C~+55°C (-14°F~+131°F) / Less than 90% RH
<b>Storage Temperature / Humidity</b>	-30°C~+60°C (-22°F~+140°F) / Less than 90% RH
<b>Input Voltage</b>	PoE(IEEE802.3af, Class3), 12VDC
<b>Power Consumption</b>	PoE: Max. 6.5W 12VDC: Max. 6W

## Mechanical

<b>Color / Material</b>	Ivory / Plastic
<b>Product Dimensions / Weight</b>	131.1(W)x28(H)x86(D)mm(5.16x1.1x3.39"), 245g(0.54 lb)

# XNB-6001

Remote Head Cam & Lens modules



CAD

Unit: mm [inch]

XNB-6001  
UNIT : mm[inch]

