



## XRN-1620B2

16CH NVR

### Benefits

- A cost-effective way to take advantage of the licence-free Deep Learning AI video analytics built into Wisenet AI cameras.
- Install wizard accessible through web interface to quickly install without monitor and keyboard directly attached.
- Wisenet AI cameras have Deep Learning analytics to detect and classify objects including people, vehicles, faces and number plates as well as object attributes such as gender, colour of clothing, glasses, bags and vehicle type.
- Single or multiple event trigger rules can include a wide range of event criteria, such as audio, fog, motion, tampering and motion detection, as well as sound classification and Intelligent Video Analytics (IVA).
- AI search filters allow the rapid discovery of footage using check box criteria to filter by object type and attributes.
- WiseStream II complementary compression technology, combined with H.265 compression, improves bandwidth efficiency by up to 75% compared to current H.264 technology.
- New look front grill optimises air flow to keep the hard disk drives cool which increases disk life and efficiency.
- Dynamic event supports future camera features without the need for a firmware upgrade.
- QR code scan on your smartphone for remote monitoring on the move.
- 16 Channels CIF to 8K resolution support or Max 16 Ch (CIF – 32MP).
- ONVIF profile S conformant.

### XRN-1620B2

#### DISPLAY

##### Network camera

Inputs	Max. 16CH
Resolution	32MP ~ CIF
Protocols	SUNAPI, ONVIF

##### Decoding

Local Display	FHD: HDMI & VGA Dual monitor / UHD: HDMI Single monitor
Multi Screen Display	[Local Monitor] 1/ 2V/ 2H/ 3V/ 4/ 6/ 8/ 9/ 13/ 16/ Sequence [Web] 1/ 2H/ 2V/ 3V/ 4/ 6/ 8/ 9
Resolution	[Local Monitor] FHD Clone mode : 32M(15fps, H.265 Only), 12M(30fps, H.265 Only), 8.3M(50fps), 1080p(240fps), D1(480fps) UHD Single mode : 32M(15fps, H.265 Only), 12M(30fps, H.265 Only), 8.3M(50fps), 1080p(240fps), D1(270fps) FHD Expand mode: 32M(12fps, H.265 Only), 12M(25fps, H.265 Only), 8.3M(30fps), 1080p(90fps), D1(200fps) Clone/Single mode : MAX 15fps when displaying more than 10CH Expand mode : Up to 9 divisions, Max 15fps when displaying more than 8CH

#### INTELLIGENT ANALYSIS

AI Search	Object Attribute	Compatible for Wisenet AI Camera
-----------	------------------	----------------------------------

#### PERFORMANCE

Operating System	Embedded	Linux
------------------	----------	-------

##### Record

Compression	H.265, H.264, MJPEG
Recording Bandwidth	Max. 140Mbps
Resolution	32MP ~ CIF
Mode	Normal, Dual Stream, Schedule(Continuous/Event), Event (Pre/Post), Bookmark
Event Trigger	Alarm Input, Video Loss, Camera Event(Sensor, MD, Video Analytics, Defocus, Audio), Dynamic Event
Event Action	e-Mail, Event Push, PTZ Preset, Alarm Out, Buzzer, Monitor Out

##### Search & Play

Playback Bandwidth	Max. 32Mbps
User	Max. 4 Users (Local 1, Remote 3)
Simultaneous playback	Max. 64CH(Local 16CH, Remote 16CH per user)
Fisheye Dewarping	CMS
Mode	Date & Time(Calendar), Event list, Text Search, Smart Search
Resolution	CIF ~ 32MP (Up to H.264 8.3MP, H.265 32MP)
Playback Control	Fast/Slow Forward / Backward, Move one step Up / Down

##### Storage

Supported HDD	Up to 10TB
HDD Slot	SATA 8ea(Max. 80TB)

##### Backup

File backup	BU/Exe(GUI), JPG/AVI(Network)
Function	Multi channel(Up to 16CH) Play, Date-Time/Title display

#### NETWORK

Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP (Server, Client), SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client)
DDNS	Hanwha DDNS
Transmission Bandwidth	Max. 140Mbps

##### Audio


Input/Output	16 CH(network)
Compression	G.711, G.726, AAC(16/48KHz)
Audio Communication	2-Way

## Key Features

- Up to 16CH (CIF to 32MPix supported)
- Max. 140Mbps network camera recording
- HDMI out
- User friendly UI / UX
- AI search support when working with Wisenet AI camera
- Dynamic Event support - New event function of cameras is available without software update
- H.265, H.264, MJPEG codec supported
- Bookmark management (Up to 100 set)
- SATA 8ea (Up to 80TB)

## Dimensions

Unit:mm(inch)



- \* The latest product information / specification can be found at [hanwha-security.com](http://hanwha-security.com)
- \* Design and specifications are subject to change without notice.
- \* Wisenet is the proprietary brand of Hanwha Techwin.

## XRN-1620B2

Max Remote Users	Search(3), Live Unicast(10), Multicast(20)	
Security	IP address filtering, User access Log, 802.1x, Encryption Device certificate(Hanwha Techwin Root CA), Signed firmware	
Web viewer		
	Supported OS	Windows 10, macOS 10.13
	Supported browser	Google Chrome, Microsoft Edge, Mac Safari, Firefox
Viewer Software	WAVE, SSM, Webviewer, Smart Viewer, Wisenet mobile Support SDK/CGI(SUNAPI) for integration to 3'rd party VMS	
<b>FUNCTIONS</b>		
Camera Setup		
	Register	Auto, Manual
	Item	IP address, Add profile edit, Bitrate, Compression, GOP, Quality, Camera MD setup (4, 8 point polygon) Camera video setup (Simple focus, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSSNR, Shutter, SSSDR, DIS), Fisheye Dewarping Mode, Hallway View Setup, Camera Webpage
PTZ		
	Control	Via GUI, Webviewer, SPC-2000
	Preset	300 Presets
Smart phone		
	Support Model	iOS, Android
	Protocol Support	RTP, RTSP, HTTP, CGI(SUNAPI)
	Control	Live 16CH(Multi-Profile Support), Playback 4CH
	Max. Remote Users	Search(3), Live Unicast(10)
Redundancy		
	Failover	N+1
	ARB	Support
Easy configuration	P2P(QR code)	
<b>INTERFACE</b>		
Front	Indicator	HDD, Alarm, Power, Record, Backup, Network
Storage	OK	
HDMI	1EA 3840x2160 30Hz	
VGA	1EA 1920x1080 60Hz	
Audio	Out 1EA	
Ethernet	RJ-45 2EA (LAN/WAN, 1Gbps)	
Alarm	In 4EA, Out 2EA	
USB	3EA(Front 2 x USB 2.0, Rear 1 x USB 3.0)	
Power inlet	AC 1EA	
<b>SYSTEM</b>		
Log	Log List	Max. 100,000 (System Log, Event Log each)
System Control	Mouse, Web, Controller (SPC-2000)	
Language	English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Swedish, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai, Vietnamese	
<b>ENVIRONMENTAL</b>		
Operating Temperature	0°C to +40°C(32 to 104 )	
Operating Humidity	20% ~ 85% RH	
<b>ELECTRICAL</b>		
Power Input	100 ~ 240 VAC ±10%; 50/60 Hz	
Power Consumption	130W	
<b>MECHANICAL</b>		
Colour / Material	Black	
Dimension (WxHxD)	440 x 89.8 x 428.4 mm	
Weight	5.71Kg	