WISENETSHB-4301HP





SHB-4301HP

Box Camera Housing

FC CUDUS CE EN



Key Features

- Material: Aluminium Die-Casting ADC 12
- Use Condition: -35°C ~ +50°C
- Weight: 2.5kg (without Bracket)
- Color: Ivory
- PoE function, Dustproof, Waterproof, IP66





SHB-4301HP

Box Camera Housing

Specifications

Environmental	
Operating Temperature / Humidity	-35°C ~ +50°C (-31°F ~ +122°F) / Less than 90% RH
Fan/Heater	Support (Heater : 5°C \pm 5°C on, 15°C \pm 5°C off / Blower : 35°C \pm 2°C on, 30°C \pm 2°C off)
Certification	IP66
Electrical	
Input Voltage	PoE(IEEE802.3at, Class4), 12VDC
Power Consumption	16W FAN(2W): 2W * 1EA HEATER(9W): 9W * 1EA
Mechanical	
Color	lvory
Material	Aluminum
Product dimensions / weight	Outside : 184(W)x127(H)x460(D)mm Inside : 99(W)x80(H)x250(D)mm
Pan / Tilt / Rotate Range	0°~360° / 0°~90°
Supported products	Box cameras (Network) We For further compatible models, please visit our website or use Toolbox