

ASR1201D ASR1201D-D

Slim Water-proof RFID Reader



Technical Specification

Model	ASR1201D	ASR1201D-D
-------	----------	------------

System

Main Processor	8 Bit
----------------	-------

Read

Read Format	13.56MHz	125KHz
-------------	----------	--------

Read Range	1cm-3cm (max.)
------------	----------------

Reading time	<0.1s
--------------	-------

Function

Tamper Alarm	Yes
--------------	-----

Interface

To Controller	RS485, Wiegand34(Wiegand 26 optional)
---------------	---------------------------------------

General

Keypad	12Keys (0-9, *, #)
--------	--------------------

LED Indicator	Yes
---------------	-----

Beep Tone	Buzzer
-----------	--------

Ingress Protection	IP55
--------------------	------

Power Supply	9V-15V DC/100mA
--------------	-----------------

Operating Temperature	-30°C to +60°C
-----------------------	----------------

Working Humidity	≤95%
------------------	------

Dimension(WxDxH)	135x47.5x16mm
------------------	---------------

Weight	0.18kg
--------	--------

Working Environment	Outdoor
---------------------	---------

Certificates

CE	Yes
----	-----

FCC	Yes
-----	-----

Features

- Support RS485, Wiegand34 protocol(Wiegand 26 optional)
- 13.56MHz(Mifare)
- 125KHz(EM-ID)
- Red and Blue LEDs
- Watch dog function ensure device free from halting
- Water-proof(Outdoor use)
- Surface/Flush mounted installation



Dimensions

