

In-ceiling Housing

									
SHP-3701F		SHD-3000F1 / SHD-3000FW1		SHD-3000F2 / SHD-3000FW2		SHD-3000F3 / SHD-3000FW3		SHD-3000F4 / SHD-3000FW4	
Operating Temperature		-10°C ~ +50°C (+14°F ~ +122°F)		-10°C ~ +50°C (+14°F ~ +122°F)		-10°C ~ +50°C (+14°F ~ +122°F)		-10°C ~ +55°C (+14°F ~ +131°F)	
Operating Humidity		0 ~ 90% RH		0 ~ 90% RH		0 ~ 90% RH		0 ~ 90% RH	
Materials	Body	Poly carbonate		Poly carbonate		Poly carbonate		Poly carbonate	
	Bubble	Poly carbonate		N/A		N/A		N/A	
Ingress Protection		N/A		N/A		N/A		N/A	
Vandal Resistance		N/A		N/A		N/A		N/A	
Dimensions (WxHxD)	External	Ø254.0 x 276.4mm (Ø10" x 10.88")		Ø224.0 x 106.9mm (Ø8.82" x 4.21")		Ø194.0 x 102.2mm (Ø7.64" x 4.02")		Ø224.0 x 106.9mm (Ø8.82" x 4.21")	
	Internal	Ø186.0 x 242.0mm (Ø7.32" x 9.53") (145 at Hou sing)		N/A		N/A		N/A	
Weight		830g (1.83 lb)		490g (1.08 lb)		350g (0.77 lb)		490g (1.08 lb)	
Input Voltage		N/A		N/A		N/A		N/A	
Power Consumption		N/A		N/A		N/A		N/A	
Color		Ivory		Ivory	White	Ivory	White	Ivory	White

* You can find applicable models with accessory selector www.hanwha-security.com/en/products/accessory-selector/

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of **Hanwha Techwin**.

Dimensions

Unit : mm (inch)

