

2010-2-PAK-RMMB

Klucz aktywacyjny-MODBUS over IP

Overview

The fire panel allows for its capabilities to be extended by use of USB dongles. These USB dongles are called PAK, which stands for Panel Activation Key. The use of the PAK will activate additional high-end feature(s) in the panel. Depending on the required functionality, separate and multiple PAKs can be used to enable these functionalities. Functionalities like number of nodes/loops, supported detector protocol, used TCP/IP communication protocol for remote monitoring, communication towards management software like BACNet or Modbus, etc, can be enabled by usage of the PAKs. The PAK is tied to the serial number of the panel, but does not have to stay connected to the panel. It can be removed once the PAK has been installed, and the feature is enabled in the panel. It is therefore recommended that PAKs stays with the panel at all time, for example in case of performing reset functions or re-installations.



Details

- Enables the Modbus protocol over Ethernet
- Compatible with panel firmware 3.5. or higher

2010-2-PAK-RMMB

Klucz aktywacyjny-MODBUS over IP

Technical specifications

Ogólne

Zgodność	USB type 2.0
----------	--------------

Fizyczne

Wymiary	22 x 70 x 5 mm (W x H x D)
Masa netto	75 g
Masa brutto	100 g
Typ montażu	W obudowie

Środowiskowe

Temperatura pracy	-5 to +40°C
Temperatura magazynowania	-20 to +50°C
Wilgotność względna	95% max. noncondensing



Będąc firmą innowacyjną, Carrier Fire & Security zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.