

In-ceiling Housing

							
		SHP-3701F SHP-1520FW	SHD-3000F1 SHD-3000FW1	SHD-3000F2 SHD-3000FW2	SHD-3000F3 SHD-3000FW3	SHD-3000F4 SHD-3000FW4	SHD-3000F5
Operating Temperature		-10°C ~ +50°C (+14°F ~ +122°F)	-10°C ~ +50°C (+14°F ~ +122°F)	-10°C ~ +50°C (+14°F ~ +122°F)	-10°C ~ +50°C (+14°F ~ +122°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (-14°F ~ +131°F)
Operating Humidity		0 ~ 90% RH	0 ~ 90% RH	0 ~ 90% RH	0 ~ 90% RH	0 ~ 90% RH	0 ~ 90% RH
Materials	Body	Poly carbonate	Poly carbonate	Poly carbonate	Poly carbonate	Poly carbonate	Aluminum, UL2820 Plenum rated
	Bubble	Poly carbonate	N/A	N/A	N/A	N/A	N/A
Ingress Protection		N/A	N/A	N/A	N/A	N/A	N/A
Vandal Resistance		N/A	N/A	N/A	N/A	N/A	N/A
Dimensions (WxHxD)	External	Ø254.0 x 276.4mm (Ø10" x 10.88")	Ø224.0 x 106.9mm (Ø8.82" x 4.21")	Ø194.0 x 102.2mm (Ø7.64" x 4.02")	Ø224.0 x 106.9mm (Ø8.82" x 4.21")	Ø224.0 x 106.9mm (Ø8.82" x 4.21")	Ø352.0 x 109.6mm (Ø13.86" x 4.29")
	Internal	Ø186.0 x 242.0mm (Ø7.32" x 9.53") (145 at Hou sing)	N/A	N/A	N/A	N/A	N/A
Weight		830g (1.83 lb)	490g (1.08 lb)	350g (0.77 lb)	490g (1.08 lb)	490g (1.08 lb)	2550g (5.62lb)
Input Voltage		N/A	N/A	N/A	N/A	N/A	N/A
Power Consumption		N/A	N/A	N/A	N/A	N/A	N/A
Color		Ivory/White	Ivory White	Ivory White	Ivory White	Ivory White	White

* You can find applicable models with accessory selector www.hanwha-security.com/en/products/accessory-selector/

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of Hanwha Techwin.

Dimensions

Unit : mm (inch)

