Product Data Sheet



YBN-R/4IS(WHT)

Conventional Intrinsically Safe Detector Mounting Base

General

The YBN-R/4IS(WHT) is a WHITE conventional detector mounting base associated with the conventional range of intrinsically safe detectors which is fully compatible with the majority of existing conventional fire alarm control panels.

Installation

The YBN-R/4IS(WHT) is supplied with square cable clamps for secure and reliable cable termination. Note that this base does not provide line continuity during detector removal (head out support). If manual call points are therefore being used, then these should be wired onto the zone first.



Standard Features

- · Low profile
- Rugged design
- Dedicated cable screen terminal
- Accepts from 1 to 2.5 mm² cables
- Quick connection via square cable clamps
- Electronics free

YBN-R/4IS(WHT)

Conventional Intrinsically Safe Detector Mounting Base

Specifications

Environmental	
Relative humidity (max - no condensation)	95% @ 40°C
Mechanical	
Colour	White
Material	ABS
Weight	51 mm
Dimentions (dia x h)	100 x 8 mm
Fixing centres	48 to 74 mm
Wire thickness (max)	2.5 mm ²

Ordering Information

Part No.	Descriptio

YBN-R/4IS(WHT) Conventional Intrinsically Safe Detector Mounting Base

n