

Free-standing 360° or 180° view and wall mounted TW beam towers

The TW, STW and STWM towers are suited for all OPTEX® AX and Smart Line™ (SL) wired, IP and wireless infrared beams models



Concealing active infrared beams in towers increases the security and flexibility of perimeter protection systems.

OPTEX Dual and Quad IR beams can be mounted directly on walls or poles, however by installing them in towers, it makes them less obvious. The number and height of the fitted beams becomes unknown to the potential intruders, enhancing this way the security level.


Additionally, the options to mount lighting or a fixed camera in a special housing on top of the towers allows a complete security system to blend nicely into its environment.

- Free standing models TW provide 360° unobstructed view for the beams, enabling back to back installation to cover a whole perimeter
- Free-standing STW models provides 180° view enabling side detection for sites where wall mount is not a possible or practical option
- Wall mounted STWM models features 180° view and flush mount
- 0.5m/1m/1.5m/2m/3m heights available
- Durable construction with extruded aluminium frame and acrylic materials
- Beams can be mounted at any height and direction in the tower
- Additional housing and fixings for lighting or fixed cameras available as options
- Anti-tamper and full fixing kit for the tower itself supplied
- Suitable for all wired, IP and wireless OPTEX AX and Smart Line (SL) models (consult us for the list of accessories needed)





Tower part numbers



Ground mounting, 360° Ground mounting, 180° Wall mounting, 180° (Flush Mount) STW050M TW50 50cm 360° Beam Tower Floor STW050 50cm 180° Beam Tower Floor 50cm 180° Wall Mount Beam Tower STW100M STW100 1m 180° Wall Mount Beam Tower TW100 1m 360° Beam Tower Floor 1m 180° Beam Tower Floor STW150M STW150 TW150 1,5m 360° Beam Tower Floor 1.5m 180° Beam Tower Floor 1.5m 180° Wall Mount Beam Tower TW200 2m 360° Beam Tower Floor (standard height) STW200 2m 180° Beam Tower Floor STW200M 2m 180° Wall Mount Beam Tower STW300M STW300 3m 180° Beam Tower Floor 3m 180° Wall Mount Beam Tower TW300 3m 360° Beam Tower Floor (lateral supports incl.)

Fixing kit for the OPTEX beam set

Two models of beam support plates are available, and the selection will depend on the OPTEX beam models to be installed. Each kit mentioned below includes two plates, one for the transmitter and one the receiver.



TWSAX

TWSAX is a kit of two plates, designed to mount the OPTEX AX-TN/TF beam models. Only one TWSAX kit is necessary per beam set.



TWSSL

TWSSL is a kit of two plates, designed to mount the OPTEX Smart Line (SL) and the AX-TFR beam models. Only one TWSSL kit is necessary per beam set.

For wireless beams, an additional battery holder would be needed, please contact us for more information or consult our beam tower guide on our website.



Common accessories



EVA/E

Tower head extension for lighting (lighting bulb not included)



Concrete floor bracket for the double sided free standing beam towers



TWH 24V

12V or 24V, 250mA, non polarity heater



TW FAN

12V, 100mA fan (TW Fan 12V) 24V, 150mA fan (TW Fan 24V)



TWAA

Anti-climb tamper



STWER

Concrete floor bracket for the STW single sided free standing beam towers



TWT

Thermostat for heater



TWT-50

Thermostat for fan (for high temperature)



OPTEX (EUROPE) LIMITED

EMEA Headquarters
T: +44 (0)1628 631 000
Dubai branch
T: +971 (0)4 501 53 94
E: marketing@optex-europe.com
www.optex-europe.com

OPTEX Security SAS

(France, French speaking North and West African countries)
OPTEX Security SAS
T: +33 (0)4 37 55 50 50
E: contact@optex-security.com
www.optex-security.com

OPTEX Security Sp. z o.o.

(Eastern Europe, CIS countries, Turkey) Optex Security Sp. z o.o. T: +48 (22) 598 06 60 E: optex@optex.com.pl www.optex.com.pl

OPTEX Technologies BV

(Benelux)
OPTEX Technologies B.V.
T: +31 70 4194100
E: info@optex.eu
www.optex.eu