

Pre-built towers for SL-QDP-BT active beams TWD-RR, STW-RR and STWM-RR series

A time saving and simplified solution for installing free-standing and wall-mounted beam towers



Pre-built 2m Tower

*Power supply optional accessory

OPTeX's prebuilt towers are designed to make the installation of towers as quick and painless as possible.

Mounting active infrared beams into towers rather than on to walls or poles, enhances the security level as it makes it very difficult for potential intruders to find out the number and height of beams installed. To encourage the use of towers without increasing the installation workload or risk of mistakes, we have introduced both two and three meter, 180° and 360°, free-standing and wall-mounted pre-built towers.

The beam towers are delivered with:

- 60m, 100m or 200m SL-QDP-BT beams (to be ordered as a separate item)
- brackets
- heaters
- tamper switch
- mounting components

Optional components that can be built in:

- power supply units
- anti-climb top tamper
- fans


Additional accessories that are available for shipping:

- concrete floor brackets for soft earth digs
- tower head extension for lighting



Tower part numbers*

TWD Double sided free standing towers



- TWD202RR** 2m 360° 1 beam per side with heater
- TWD204RR** 2m 360° 2 beams per side with heaters
- TWD306RR** 3m 360° 3 beams per side with heaters

TW

STW single sided free standing towers



- STW201RR** 2m 180° 1 beam with heater
- STW202RR** 2m 180° 2 beams with heater
- STW303RR** 3m 180° 3 beams with heater

STW

STWM single sided wall mounted towers



- STWM201RR** 2m wall mount 180° 1 beam with heater
- STWM202RR** 2m wall mount 180° 2 beams with heater
- STWM303RR** 3m wall mount 180° 3 beams with heaters

STWM

*3 Meter towers are made to order

Beam units (choose the right unit for the distance between towers)



- SL-200-QDP-BT** 60 meter quad beam unit
- SL-350-QDP-BT** 100 meter quad beam unit
- SL-650-QDP-BT** 200 meter quad beam unit

SL-QDP-BT

Additional components†



TWAA

Anti climb top tamper



TWMR FAN KIT

12 Volt fan kit with thermostat



DC12V

12Volt Power supply 1.8Amp with bracket

Common accessories



TWE

Tower head extension for installation of light



TWEB

Concrete floor bracket for 360° double sided free standing towers



STWEB

Concrete floor bracket for 180° free standing

*Please note beam units are priced separately. † Specifications and design are subject to change without prior notice.



OPTEX (EUROPE) LIMITED
 EMEA Headquarters
 T: +44 (0)1628 631 000
 Dubai branch
 T: +971 (0)4 501 53 94
 E: marketing@optex-europe.com
 www.optex-europe.com

OPTEX Security SAS
 (France, French speaking North and West African countries)
 OPTEX Security SAS
 T: +33 (0)4 37 55 50 50
 E: contact@optex-security.com
 www.optex-security.com

OPTEX Security Sp. z o.o.
 (Eastern Europe, CIS countries, Turkey)
 Optex Security Sp. z o.o.
 T: +48 (22) 598 06 60
 E: optex@optex.com.pl
 www.optex.com.pl

OPTEX Technologies BV
 (Benelux)
 OPTEX Technologies B.V.
 T: +31 70 4194100
 E: info@optex.eu
 www.optex.eu