

# NVD1505DH-4I-4K

## Ultra-HD Network Video Decoder



### Features:

- Standard 2.5U case, elegant appearance
- Plug-in board design, easy to use and maintain
- H.265+/ H.265/ H.264/ MPEG4/ MPEG2/ MJPEG video decoding
- Ultra-high decoding ability, up to 32 Megapixels
- 2ch HDMI and 2ch DVI-I input, supports 4K collection
- Supports 1/4/6/8/9/16/25/36 and free split
- Supports alarm, RS232, RS485
- Splicing screens control for zoom/merge/roam/overlay
- Support redundant power, stable and reliable



### Technical Specification

#### System

Processor	Embedded processor
Operating System	LINUX
Slot	1 Main board, 2 Decoding board(6CH), 1 Collection board, 2 Blank panel

#### Performance

Video Format	H.265+/ H.265/ H.264/ MPEG4/ MPEG2/ MJPEG
Audio Format	PCM/G711/AAC
Decoding Capacity Separately	Port1,2,3   Port4,5,6   Port7,8,9   Port10,11,12   Port 13,14,15 1CH@32MP(25fps)/3CH@12MP(15fps)/4CH@8MP/16CH@1080P/64CH@D1
Total Video Decoding	5CH@32MP(25fps)/15CH@12MP(15fps)/20CH@8MP/40CH@5MP/50CH@3MP/80CH@1080P/180CH@720P/320CH@D1
Decoding Resolution	32MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P/960H/D1/HD1/2CIF/CIF/QCIF
Video Output	15ch HDMI
Display Resolution	3840×2160(30fps)/2560×1600/1920×1080/1280×1024/1280×720/1024×768
Video Input	2 HDMI, 2 DVI-I
Collection Resolution	3840×2160(HDMI 2)/1920×1080/1600×1200/1680×1050/1440×900/1400×1050/1366×768/1280×1024/1280×960/1280×800/1280×720/1152×864/1024×768/800×600, etc
Audio Output	15ch HDMI (embedded)
Bi-directional Talk	1 Pair 3.5mm jack (reserved) (2.0V Line in/50mV Mic in/10KΩ, 2.0V/16Ω out)

Alarm Input/Output	2CH/1CH(30V DC 1A, 125V AC 0.5A)
Communication Interface	2 RJ45 network port (10M/100M/1000M)
RS232	3 (1 DB9, 2 RJ45)
USB	3 (2 USB3.0, 1 USB2.0)
RS485	1

#### Others

Power Supply	AC100-127V, 200-240V, 47Hz-63Hz
Power Consumption	≤180W
Working Temperature	-10C~+55C
Working Humidity	10% ~ 95%, 86Kpa ~ 106Kpa
Unit Dimension	2.5U, 440×436.6×110mm(17.32 × 17.19 × 4.33 inch), (W*D*H)
Weight	11.33kg(24.98 lb)

Dimensions(mm)

