



Product Code

F07470

DUOX PLUS SKYLINE DISPLAY

Reference

7470

EAN

8424299074702

Description.

Description

The Duox **Plus display module** allows searching and viewing the list of neighbors (electronic directory) using the navigation buttons (arrow keys), in addition to reporting on the status of the communication.

The call to the home can be made in two ways:

- by entering the corresponding code assigned to the home + the "bell" key.
- by searching the user's electronic directory (navigation buttons) and once found by pressing the "bell" key.

The navigation buttons also allow you to move through the programming menu.

SKYLINE plate

The SKYLINE electronic intercom and video intercom panel is a robust and elegant panel, which stands out for its durability and beauty, resistance and reliability.

SKYLINE is Fermax's line of electronic and video intercom entrance panels with a continuous profile and modular composition. The line is made up of 8 frames of different sizes where the different modules fit easily: pushbuttons, card holder, camera, amplifier, access control, etc. The frames allow a certain number of modules to be attached. There are two sizes of modules: V and W. W modules are twice the size of V modules.

Module Measurements.

- Module V: 105.2x47.5 mm (width-height).
- Module W: 105.2x95 mm (width-height).

It is possible to combine two or more plates, as long as they are from the same series, to have a greater capacity of buttons and accessories.

System: DUOX PLUS (2-wire digital)

Technical Details

IPK-437

Display Technical Specifications:

- Size: 3.5 inches
- Format: 4:3
- Resolution: 320 x 240 pixels
- Colors: 262,000
- Contrast ratio: 500/1
- Viewing direction: 12 o'clock
- Luminance (cd/m2): 400 nits
- Viewing angle: 160H/160V
- Backlight: 6 LED diodes
- Directory capacity: 10,000 users.
- Supply voltage (via CN1):
- 5 V input (pin 1) with a tolerance of 5%.
- PWR input: 12 Vdc + 5% (DUOX)
- Total consumption: 88 mA +10% (STANDBY); 134 mA +10% (TFT ON)
- Operating temperature: -25°C, 70°C
- Relative humidity: 5% - 95%
- Includes Wiegand-26/DataClock input port through the CN2 Reader connector. Compatible with 7440 reader

Display Module Measurement.

- Module W: 105.2x95 mm (width-height).

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.3262	(height x width x depth) cm	Technologie
	13,5x10x6	DUOX

Manuals

- 970005F Manual Mode LECTURE-ECRITURE V08_17.pdf
- 97830E Manual software DISPLAY PLUS V04_22.pdf
- 97830F Manual software DISPLAY PLUS V04_22.pdf
- 97830I Manual software DISPLAY PLUS V04_22.pdf
- 97869Ah_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf
- 97869Eh_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf
- 97869Fh_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf
- 97869Ih_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf
- 97869Ph_DISPLAY_SKYLINE_DUOX_PLUS_V01_24.pdf