



Product Code

F09545

MEET LIFT CONTROL GATEWAY

Reference EAN

9545 8424299095455

Description.

Description

The elevator control gateway is a device between the building intercom system and the elevator control system. There are 5 modes defined in the elevator control system:

- The owner calls the elevator to go up
- The owner calls the elevator to go down
- The owner enables the apartment in which he resides for visits
- The owner opens the door when he receives a plate call.
- It asks for the status of the elevator and shows it on the screen. This device has 6 LEDs on the cover. It can display the command information and the STATUS + APARTMENT OF THE HOMEOWNER. If applicable, the ref. F01616 10 OUTPUT RELAY DECODER, must be configured in the first instance. Each of the NO/NC relays of the F01616 decoder is assigned to a floor, and this information must be recorded in an Excel file. Special software will be used to upload this information to the gateway.

Elevator control function compatible with digital panels; Not compatible with 1-line Milo boards

Technical Details

Consumption:

• At rest: 60mA

• Operating: 110mA

Operating voltage:

• 12 Vdc



Funcionament condition:

• Temperature: -40 oC - 55 oC

• Humidity: 10 – 93% (No condensation)

Dimensions:

• 145×90×45mm

Details.

Product measurements (height x Weight (kg) width x depth) mm 0.2437

145 X 90 X 45

Packaging measurements (height x width x depth) cm

6,3x17,7x9,5

Video Door Entry system

Technologie

MEET

Manuals

- 970140Eb Man control ascensores MEET V09_21.pdf
- 970140lb_Man_control_ascensores_MEET_V09_21.pdf

Declaration of conformity

• DOCF09545EN.pdf