



Product Code F01445 KIN TOUCH PANEL MEET

Reference

1445

EAN 8424299014456

Description.

Description

FUNCTIONS

- CALL TO HOUSING Visitors can call the desired Home from both a General Entrance and a Block Entrance. It is possible to use numbers (0-9) and letters (AH).
- AGENDA Visitors will also be able to locate a call by searching for the neighbor's name in the electronic directory. The directory has a capacity of 10,000 users (name and home number). The agenda management is carried out through the integrated webserver.
- CALL TO CONCIERGE If a visitor or neighbor needs assistance from the concierge, they can make a call from the panel (general or block) to any of the guard units assigned to them. It is possible to assign up to 2 of the 98 possible guard stations to each panel.
- ADDITIONAL RELAYS It is possible to install up to 4 additional relays (a Ref. 1491 module is required). Neighbors will be able to open additional doors (garages, hallways, etc.) when they receive a call from one of the entrances to their block.
- ACCESS VIA PIN CODE It is possible to define up to 8 access codes (pin), so that users can open the door. These codes can be 4 to 6 digits and are managed through the board's own webserver.



- FACIAL RECOGNITION Authorized neighbors can be identified by simply standing in front of the plate and pressing the FACIAL ID button. The door will open automatically. This operation will also disconnect the alarm in your own home.
- ACCESS CONTROL The board includes a Mifare card reader, and can control up to 100,000 cards. The management of the cards is carried out through the MEET Management Software. It is also possible to connect third-party readers to the board that use the Wiegand 2 protocol (input and output functions).
- IP CAMERAS It is possible to configure up to 4 IP cameras so that they can be used as an auxiliary camera for any monitor in the same block. These cameras would serve to track visits through hallways or common areas of the development.
- VIDEO STREAMING Constant transmission of the license plate camera via RTSP protocol is possible, so that it can be used by third-party devices (video recorders and/or CCTV security cameras). It is not possible to send RTSP video and do facial recognition simultaneously.
- ANTI-SABOTAGE The plate is protected against acts of vandalism (disassembly attempts). In the event that the panel is separated from its location, an alarm will be sent to the associated concierges and the MEET Management Software. Compatible with Elevator Control Function

Technical Details

System:

- CPU: Quad-core Cortex[™]-A7 1.5GHz
- GPU: Mali400MP2
- FLASH: 8GB eMMC Flash
- SDRAM: 1GB DDR3L Screen:
- 10.1" color TFT
- Resolution 1024 x 600 pixel
- Viewing angle: 130° H, 140° V
- Contrast: 800/1
- Brightness: 300cd/m2 Audio:
- Codec G.711/G 729 Camera:
- 1/3" CMOS Color
- 120° diagonal Lens, Horizontal 105°, Vertical 55°
- 1280 x 720 pixel
- Minimum illumination: 0.5 LUX. Automatic activation of LEDs
- AWB Electrical consumption:
- Standby: 250 mA
- Operating: 1000 mA
- With active heater (*): 1500 mA Voltage:
- 12 Vdc
- PoE (*) Connectivity:



- RJ-45 Ethernet Connector
- RS485 connection port for elevator relay and control module.
- Wiegand-26 connection for exterior access control reader.
- Remote configuration and management through webserver.

Environmental characteristics:

- Temperature: -40 oC.. + 55 oC
- Humidity: 10 90% (non-condensing)
- IP54

Details.

Product measurements (height x	Weight (kg)	Packaging measurements	Video Door Entry system
width x depth) mm	2.2968	(height x width x depth) cm	Technologie
405 X185 X 50		14x46,5x25,5	MEET

Access Control Technology

PROXIMIDAD

Manuals

- 970162Aj_Manual_instalador_Placa_KIN_V07_22.pdf
- 970162Ej_Manual_instalador_Placa_KIN_V07_22.pdf
- 970162Fj_Manual_instalador_Placa_KIN_V07_22.pdf
- 9701621j_Manual_instalador_Placa_KIN_V07_22.pdf
- 970162Pj_Manual_instalador_Placa_KIN_V02_24.pdf
- 970162Rj_Manual_instalador_Placa_KIN_V07_22.pdf
- 970162Tj_Manual_instalador_Placa_KIN_V07_22.pdf
- 970188d_Guia_rap_Instalacion_Placa_KIN_V06_24.pdf

Declaration of conformity

• DOCF01445EN.pdf

Accessories

Fermax / Products



Actualizado el 2024-07-23 05:01



F01449 KIN PANEL FLUSH BOX MEET