



Product Code

F01491

MEET 4 RELAY MODULE

Reference

EAN

1491

8424299014913

Description.

Description

Meet panel 4 relay module, running under standard Modbus protocol, makes Meet monitors able to extend door release to 4 additional relays or doors. It works as a slave device connected to the RS-485 port of panel #1 of each block.

Technical Details

Feeding:

- 7-26 Vdc (12Vdc recommended)
- Standby: 0.28W
- Maximum: 5.5W

Connections:

- RS-485 Modbus Bus
- Outputs of the 4 relays: COM/NO/NC

Operational:

- Relay contacts: 220V/5A
- Status LEDs:

- Power: On if powered.
- RUN: Flashing after feeding.
- LNK: Receiving a package at the last minute.
- ACT: activity on the RS-485 bus.
- Relay activated: CH1-CH4

Work environment:

- Temperature: -40 oC .. +55 oC
- Humidity: 10 – 95% (Non-condensed)
- IP: 51

Dimensions:

- 115(W) x 90(H) x 40(D)m
- Mounting on 35 mm DIN rail

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
115 X 90 X 40	0.21118	6,3x17,7x9,5	MEET

Manuals

- 970086E Modulo 4 reles MEET ref 1491 V10_21.pdf
- 970086I Modulo 4 reles MEET ref 1491 V10_21.pdf

Declaration of conformity

- DOCF01491EN.pdf