



Product Code

F953303

1/W MILO VIDEO PANEL BLACK MEET

Reference

953303

EAN

8424299953335

Description.

Description

1L MEET **PoE VIDEO CARD** without proximity reader.

SPECIFICATIONS

- Aluminum profile
- Tempered glass
- High definition color camera
- Low consumption
- Extended operating range
- Modular Linux-based platform
- Remote Firmware Update

FUNCTIONS

- CALL TO APARTMENT Visitors can call the apartment associated with the plate.

- CALL TO CONCIERGE It is possible to make calls for assistance to the concierge associated with the panel.

REFERENCES

- Ref. 9533 1L MEET VIDEO CARD
- Ref. 9534 1L MEET VIDEO CARD (+ PROXIMITY READER)
- Ref. 9543 FLUSH BOX – S MEET
- Ref. 9519 SURFACE BOX – S MEET (Stainless steel)
- Not compatible with Elevator Control function

Technical Details

System:

- CPU: ARM Cortex-A7 1.2GHz
- FLASH: 128M
- SDRAM: 64M Audio:
- G.711 codec
- Audio level 17.7 dB Camera:
- 1/3" CMOS Color
- 120° diagonal lens: 100°(H), 52°(V)
- 1 Mega Pixels
- 0.5 LUX of minimum illumination.
- AWB LED:
- White LED
- LM 60 mA Min. 24, Type. 26
- Angle 201/2: 120 Consumption:
- Standby: 125mA
- Operating: 250mA
- Operating voltage: 12 Vdc Connectivity:
- RJ-45 Ethernet Connector
- Connector for exit button and door open sensor
- Door opening relay connection NO, NC, C
- Built-in web server for remote configuration and management. Funcionament condition:
- Temperature: -40°C – 55°C
- Humidity: 10 – 90%
- IP54
- IK 07

CONNECTIONS

- RJ-45 10/100 Base-T Ethernet
- +, -, : 12 Vdc Power input
- BS, -, NA, SP: Exit button and door open sensor
- NO, C, NC: Door opening relay terminals
- 485+, 485-: RS485 serial port

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.8115	(height x width x depth) cm	Technologie
	8x25,5x16,5	MEET

Manuals

- 970137Eg Man Inst Placa 1L MEET V07_22.pdf
- 970137lg Man Inst Placa 1L MEET V07_22.pdf
- 970139Ec Man Inst APP MEET V04_22.pdf
- 970139lc Man Inst APP MEET V04_22.pdf
- 970139Pc_Man_Inst_APP_MEET_V02_24.pdf

Declaration of conformity

- DOCF953303EN.pdf