



Product Code

F03267

DUOX PLUS RELAY

Reference EAN
3267 8424299032672

Description.

Description

The DUOX PLUS Relay allows DUOX PLUS installations to have a potential-free relay, with several configurable operating and activation modes:

- Activation of the relay through commands generated from the home terminals, panels or concierges.
- External activation using pushbuttons, additional external switches, etc.

The DUOX PLUS Relay can be installed anywhere on the DUOX PLUS bus.

It is possible to install one or more relays: per apartment, block or installation.

System: DUOX PLUS (2-wire digital).

Technical Details

- Power supply: 18 - 24 Vdc (non-polarized, through BUS INPUT or BUS OUTPUT).
- Consumption:
 - At rest: 1.24 W.
 - Maximum: 4.4W.
- Operating temperature: [0.40°C].
- IP: 20.
- (+12V): Auxiliary voltage output 12Vdc (max. 300mA).
- Potential-free relay contacts:

- C: Common.
- NC: Normally closed.
- NO: Normally open.
 - Maximum current: 3A.
 - Maximum voltage: 250VAC or 30VDC.

Details.

Weight (kg)	Packaging measurements	Video Door Entry system
0.3703	(height x width x depth) cm	Technologie
	7,5x23x17,8	DUOX

Manuals

- 97821c_Rele_DUOX_PLUS_ref_3267_V01_24.pdf
- 97822Ac Man Avanzado Rele DUOX PLUS ref 3267 V11_20.pdf
- 97822Ec Man Avanzado Rele DUOX PLUS ref 3267 V11_20.pdf
- 97822Fc Man Avanzado Rele DUOX PLUS ref 3267 V11_20.pdf
- 97822Ic Man Avanzado Rele DUOX PLUS ref 3267 V11_20.pdf
- 97822Pc Man Avanzado Rele DUOX PLUS ref 3267 V11_20.pdf

Declaration of conformity

- DOCF03267EN.pdf