



Product Code

F09455

DUOX PLUS VEO DDA 4.3" MONITOR

Reference

9455

EAN

8424299094557

Description.

Description

The VEO monitor is made of high-impact ABS plastic. Textured finish for easy cleaning and UV protection to make it more resistant to sunlight. VEO includes a 4.3" wide color screen (16:9). The unique and exclusive design of the headset incorporates a magnet that makes it easier for the user to position it, ensuring correct hanging at the end of the conversation. Its balanced line design Puras is distinctive, modern and minimalist. VEO integrates into the environment. When a call is received, the image appears automatically. When the handset is picked up, the conversation with the visitor begins. The image automatically disappears after 90 seconds or when the phone is hung up. the headset. To open the door press the button.

ACCESSORIES:

- 9447 VEO/VEO-XS DUOX MONITOR CONNECTOR For mounting the monitor on the wall surface.
- 9410 VEO MONITOR DESKTOP SUPPORT Fermax desktop supports allow you to answer a call from the outdoor panel, from your office desk, without having to interrupt your work. Made of the highest quality stainless steel (AISI 316L). It also requires the corresponding connector.
- 3389 LARGE UNIVERSAL FRAME 210X240 Extra flat format, made of high-impact ABS plastic, has a fine textured finish. In

replacement, it allows to fill the gap left by previous teams. Dimensions 210 x 240 x 10 mm.

Technical Details

GENERAL CHARACTERISTICS

- Technology: DUOX PLUS (non-polarised 2 wire full digital system)
- Audio/Video system: Audio/Video Color
- Set-up (Installation): Surface mounted (order connector ref. 9447 separately)
- Desktop support: Yes (ref. 9410)
- Handset with magnet to facilitate the hang up: Yes
- Induction loop : Yes
- Screen dimensions: 4,3" (Panoramic 16:9)
- Screen resolution (H x V): 480 x 272
- Color of the product: Matt white
- Number of pushbuttons: 4
- Kind of pushbuttons: Mechanical (silicone)
- Number of leds for lighted indications: 1 (red with 3 states: always ON, slow/fast blinking)

PROGRAMMING OF THE TERMINAL ADDRESS

- From the terminal: From the OSD menu
- From the outdoor panel or guard unit: Yes
- From the outdoor panel throughout the apartment door bell: Yes

FEATURES

- Automatic picture capture when the visitor calls (PHOTOCALLER): Yes (1 photo/call, until 150 photos, 368 x 288 pixels). This feature can be enabled by the user. Disabled by default.
- Guard unit call: Yes (by means of the door release button)
- Auto-on: Yes (with 3 outdoor panels/cameras)
- OSD menu: Yes
- Additional function F1: Yes (Button F1 sends a negative and/or command)
- Additional function F2: Yes (it only sends command, no negative)
- Apartment door bell differentiated from the outdoor panel: Yes
- Connection for additional devices (call extension, light/buzzer activator, etc.): Yes (ref. 2040, ref. 2438, ref. 3267)
- Additional terminals on the same address: Yes, max. 2 additional terminals (additional power supply can be required)
- Doormatic (automatic door release for offices, etc.): No

ADJUSTMENTS

- Date and time: Yes

- Ring tones selection: Yes (5). Configurable for Block Panel 0, Block Panel 1, General Entrance Panel 0 and Concierge unit.
- Call volume control: Yes (10 levels by OSD menu)
- Do-not-disturb mode: Yes (by OSD menu) + Red led indication
- Audio volume control: Yes (10 levels by OSD menu)
- Brightness, color and contrast control: Yes (by OSD menu)

TECHNICAL FEATURES

- Product dimensions (width x height x depth) mm: 200 x 200 x 23 (44 including handset)
- Time to answer or open the door since the call is done: 30 s.
- Conversation time: 90 s.
- Conversation privacy: Yes
- Voltage: 18-24 Vdc
- Maximum consumption: 5.2 W
- Standby consumption: 0.8 W
- Working temperature (°C, °F); Humidity: [-5°C, +40°C][23°F, 104°F]; [0%, 90%]
- Line adaptor included in the terminal: Yes (A, C, default position OFF)
- Connections: Bin, Bin, Bout, Bout, -, A+, F1, T

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
200 x 200 x 44	0.5449	5,1x22,2x20,7	DUOX

Manuals

- 970143Ac_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970143Ec_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970143Fc_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970143Ic_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970143Pc_Guia_rap_Usuario_Monitor_VEO_V05_23.pdf
- 970159c_Monitor_VEO_duox_NEW_V05_23.pdf
- 970160b_Guia_rap_monitor_VEO_duox_NEW_V05_23.pdf

Accessories



F09447

DUOX PLUS CONNECTOR



F03389

UNIVERSAL FRAME LARGE



F09410

VEO MONITOR DESKTOP SUPPORT

Video formativo

- <https://youtube.com/playlist?list=PLf1YNFmssC37H-1CN64lo6ND28rmVsQit>