



Network

Dome

# XNV-8080RSA

5MP Stainless IR Dome Camera



## Key Features

- Max. 5Megapixel (2560x1920) resolution
- 3.9 ~ 9.4mm (2.4x) motorized varifocal lens
- Max. 30fps@all resolutions (H.265 / H.264)
- H.265, H.264, MJPEG codec supported, Multiple streaming
- Day & Night (ICR), WDR (120dB), Defog
- Loitering, Directional detection, Tampering, Audio detection, Digital auto tracking, Fog detection, Sound classification
- Motion detection, Handover
- SD/SDHC/SDXC memory 2slots (Max. 512GB)
- Hallway view, WiseStream II support
- IR viewable length 50m
- IP66, IP6K9K, IK10+, NEMA4X
- LDC, PoE support

## Compatible Accessories (Optional)



SBP-300HMS6



SBP-300WMS1



SBP-300WMS



SBP-300PMS



SBP-300KMS



# XNV-8080RSA

5MP Stainless IR Dome Camera

## Specifications

### Video

<b>Imaging Device</b>	1/1.8" CMOS
<b>Resolution</b>	2560x1920, 2560x1440, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
<b>Max. Framerate</b>	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps/25fps(60Hz/50Hz)
<b>Min. Illumination</b>	Color: 0.07Lux(F1.3, 1/30sec) BW: 0Lux(IR LED on)
<b>Video Out</b>	CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation USB: Micro USB Type B, 1280x720 for installation

### Lens

<b>Focal Length (Zoom Ratio)</b>	3.9~9.4mm(2.4x) motorized varifocal
<b>Max. Aperture Ratio</b>	F1.3(Wide) ~ F2.4(Tele)
<b>Angular Field of View</b>	H: 93°(Wide)~38°(Tele) V: 68°(Wide)~29°(Tele) D: 120°(Wide)~48°(Tele)
<b>Min. Object Distance</b>	0.5m(1.64ft)
<b>Focus Control</b>	Simple focus
<b>Lens Type</b>	DC Auto Iris, P iris

### Pan / Tilt / Rotate

<b>Pan / Tilt / Rotate Range</b>	0~354 / 0~67 / 0~355
----------------------------------	----------------------

### Operational

<b>Camera Title</b>	Displayed up to 85 characters
<b>Day &amp; Night</b>	Auto(ICR)
<b>Backlight Compensation</b>	BLC, HLC, WDR
<b>Wide Dynamic Range</b>	120dB
<b>Digital Noise Reduction</b>	SSNR V
<b>Digital Image Stabilization</b>	Support
<b>Defog</b>	Support
<b>Motion Detection</b>	8ea, 8point Polygonal zones
<b>Privacy Masking</b>	32ea, 4point polygonal zones - Color : Gray, Green, Red, Blue, Black, White - Mosaic
<b>Gain Control</b>	Low / Middle / High
<b>White Balance</b>	ATW / AWC / Manual / Indoor / Outdoor
<b>LDC</b>	Support
<b>Electronic Shutter Speed</b>	Minimum / Maximum / Anti flicker (2~1/12,000sec)
<b>Video Rotation</b>	Flip, Mirror, Hallway view(90/270)
<b>Analytics</b>	Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Digital auto tracking, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification
<b>Alarm I/O</b>	Input 1ea / Output 1ea
<b>Alarm Triggers</b>	Analytics, Network disconnect, Alarm input

<b>Alarm Events</b>	File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC or NAS recording at event triggers Alarm output Handover
<b>Audio In</b>	Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm
<b>Audio Out</b>	Line out, Max.output level: 1Vrms
<b>IR Viewable Length</b>	50m(164.04ft)

## Network

<b>Ethernet</b>	RJ-45(10/100BASE-T)
<b>Video Compression</b>	H.265/H.264: Main/Baseline/High, MJPEG
<b>Audio Compression</b>	G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz
<b>Smart Codec</b>	Manual(5ea area), WiseStream II
<b>Bitrate Control</b>	H.264/H.265: CBR or VBR MJPEG: VBR
<b>Streaming</b>	Unicast(20 users) / Multicast Multiple streaming(Up to 10 profiles)
<b>Protocol</b>	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
<b>Security</b>	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access Log 802.1X Authentication(EAP-TLS, EAP-LEAP)
<b>Application Programming Interface</b>	ONVIF Profile S/G/T SUNAPI(HTTP API) Wisenet open platform

## General

<b>Webpage Language</b>	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Greek, Hungarian
<b>Edge Storage</b>	Micro SD/SDHC/SDXC 2slot 512GB
<b>Memory</b>	1024MB RAM, 512MB Flash

## Environmental & Electrical

<b>Operating Temperature / Humidity</b>	-40°C ~ +55°C(-40°F ~ +131°F) / Less than 90% RH
<b>Storage Temperature / Humidity</b>	-50°C ~ +60°C(-58°F ~ +140°F) / Less than 90% RH
<b>Certification</b>	IP66, IP6K9K, NEMA4X, IK10+
<b>Input Voltage</b>	PoE(IEEE802.3af), 12VDC, 24VAC
<b>Power Consumption</b>	PoE: Max 12.95W 12VDC: Max 11.5W 24VAC: Max 14W

## Mechanical

<b>Color / Material</b>	Silver / Stainless(SUS316L)
<b>Product Dimensions / Weight</b>	Ø162x120.5mm(Ø6.38x4.74") / 2.8kg(6.17lb)

## Certifications & Standards

<b>EMC</b>	FCC 47 CFR 15 Subpart B Class A ICES-3(A)/NMB-3(A) CE/UKCA - EN 55032 Class A, EN 50130-4 VCCI CISPR 32 Class A RCM AS/NZS CISPR 32 Class A KS C 9832 Class A, KS C 9835
<b>Safety</b>	UL 60950-1, CAN/CSA C22.2 NO. 60950-1 IEC/EN 62471

<b>Environment</b>	IEC/EN 63000 IEC/EN 60529 IP66, ISO 20653 IP6K9K, IEC/EN 62262 IK10+ NEMA 250 type 4X NSF/ANSI 169-2016: Special purpose food equipment and devices
--------------------	--

**DORI (EN62676-4 standard)**

<b>Detect (25PPM/ 8PPF)</b>	Wide: 48.6m(159.41ft) / Tele: 148.7m(487.85ft)
<b>Observe (63PPM/ 19PPF)</b>	Wide: 19.4m(63.76ft) / Tele: 59.5m(195.14ft)
<b>Recognize (125PPM/ 38PPF)</b>	Wide: 9.7m(31.88ft) / Tele: 29.7m(97.57ft)
<b>Identify (250PPM/ 76PPF)</b>	Wide: 4.9m(15.94ft) / Tele: 14.9m(48.78ft)

# XNV-8080RSA

5MP Stainless IR Dome Camera



CAD

Unit: mm [inch]

