

O2T/F multisensor fire detector IQ8Quad with isolator



Part-No.: 802383 Approval: VdS

In addition to smoke detection with the conventional O²T multisensor technology, the detector is provided with a built-in flash lamp. Detection

Multisensor detectors with two built-in optical smoke sensors with different scattered light angles as well as additional heat detector sensor evaluation for detecting everything from smouldering fires to open fires with consistent response performance. Smoke sensor signal identification to ensure smoke classification and reduction of false alarms caused, for instance, by water vapour or dust. Each detector is provided with an integrated isolator. Alarm signalling

The alarm signalling device is activated by the control panel. No further short address needs to be allocated. It is programmed with tools 8000 as of software version 1.05.

Features:

- The reliable O2T multisensor principle for consistent response performance at the highest level of security against false alarms
- · Individual control of the beacon
- · Loop powered no need for external power supply
- · No additional short address
- · Automatic synchronization of various IQ8Quad alarm signaling devices
- · High flash energy

Common technical data

Operating voltage 8 ... 42 V DC Quiescent current @ 19 V DC 75 µA Quiescent current @ FACP battery approx. 400 µA 10 mA ... 20 mA Alarm current

Load factor 2 Lighting energy approx. 3 Y

Luminous intensity max. 15.8 cd peak / 2.63 cd effective

Signal flashing lamp Area to be monitored 110 m² Height to be monitored 12 m

Air velocity 0 m/s ... 25,4 m/s Application temperature -20 °C ... 65 °C Storage temperature -25 °C ... 75 °C < 95 % Air humidity

Type of protection IP43 (with base + options)

Material ABS plastic

Color white, similar to RAL 9010

Weight approx. 145 g

Detector specification EN 54-7:2006/-5 B:2000/ -17:2005, CEA 4021

Dimensions Ø: 117 mm H: 59 mm **Declaration of Performance** DoP-20193130701

Not suitable for application in detector base Part No. 805591!

Accessories:

767800 Mounting bracket

Phone: +49 2131 40615 600

Faximile: +49 2131 40615 606

805590 Standard detector base for IQ8Quad © 2024 Honeywell International Inc. Subject to change without notice!