



Product Code

F05560

ONE TO ONE W/IND. LOOP V MODULE MARINE

Reference

5560

EAN

8424299055602

Description.

Description

Induction loop amplification system module (teleloop) used in combination with VDS and DUOX audio and video amplifier modules (including open door indication speech synthesis) to enable use by people wearing hearing aids (equipped with T selector). Connection to the amplifier module via the included multi-cable.

The "OneToOne" module with inductive loop shows the status of the board using 4 LED icons.

These icons symbolize:

- Call
- Conversation
- Door Opening
- Channel busy.

In addition, each of the sounds and audio reproduced by the amplifier are emitted by the inductive loop to the disabled people's devices.

Technical Details

MODULE CONNECTORS

- This module is compatible with the following systems: VDS and DUOX. The wiring of the connectors will depend on the chosen system.
- CN1: Input connector for push buttons or card holder (3 ways).
- CN2: Not in use (7 tracks).
- CN3: Input connector for status LEDs (5 ways).
- CN4: Output connector for push buttons or card holder (3 ways).
- CN5: Not in use (7 tracks).

- CN7: Input connector for amplifier speaker.
- RG1: Power strip.

TECHNICAL CHARACTERISTICS

- IP33 / IK06

Feeding:

- VDS: 18 Vdc
- DUOX: B, B

The loop is fed from the RG1 strip.

Consumption**ONE TO ONE**

- YOU
 - active audio: 350mA.
 - maximum: 1A.
- DUOX:
 - active audio: 315mA.
 - maximum: 1A.

Operating temperature: [-25 , +70 °C]

Module Dimensions: 105.2 x 47.5 mm (width x height).

Details.

Weight (kg)

0.1594

Packaging measurements

(height x width x depth) cm

6,1x13,5x10

Video Door Entry system

Technologie

GENERICA

Manuals

- 970111b Modulo
OneToOne BUCLE
V03_20.pdf