



Product Code

F73612

DUOX PLUS DIRECT CITY AUDIO PANEL

Reference

73612

EAN

8424299736129

Description.

Description

Installed in the accesses to the building, it allows communication with the dwellings, door opening, call to the guard, etc..

CityLine panel.

Cityline is the "monoblock profile" outdoor panel line for buildings.

This panel model is more robust and of greater aesthetic and functional quality. It integrates, in its video door entry version, the audio and video functions in the same module.

It is characterized by its curved-convex profile maintaining the same characteristics of its predecessor the City Classic. There is total compatibility between both models, ensuring their immediate replacement and replacement.

It is made of anodized aluminium, highly resistant to weather and climate changes (IP43 IK07). It incorporates new materials such

as chrome-plated zamak in the covers and the pushbuttons. The front of the amplifier is made of aluminium and the interior is protected by a stainless steel grid

The Cityline panel does not include the flush or surface box. This must be ordered separately.

It is possible to combine two or more panels, as long as they are of the same series. To ensure that they are perfectly matched, one set of joining bolts be used for every two panels installed between their flush-mounted boxes.

Aluminium colour.

Backlit keypad.

System: DUOX PLUS (2-wire digital)

Technical Details

DIRECT panels have a backlit keypad for calling homes.

The call to the flat is made by entering the corresponding code assigned to the flat + the "bell" key.

It is recommended that a Directory Board be added to show the list of addresses of the homes.

Access Control: through the numeric keypad it incorporates access control functions by means of a keypad code (previously programmed). The keypad allows 1 code to open the door.

Series 5 panel.

- Panel size: 130x246 mm (width-height).
- Flush box measurements: 115x233x45 mm (width-height-depth).
- Surface box measurements: 130x246x33 mm (width-high-deep).

Power supply: 18-24 Vcc

Consumption:

- stand-by: 94 mA.
- Active audio: 550 mA.

IP43 IK07

Audio power home-street direction: 2W

Audio power street-wise: 0.15W

Volume adjustable in both directions.

Operating temperature: -25 to 70 °C

Details.

Weight (kg)

0.986856

Packaging measurements

(height x width x depth) cm

6,9x20x26,7

Video Door Entry system

Technologie

DUOX

Manuals

- 970052c Placas Direct
VIDEO DUOX PLUS
V07_21.pdf