



# SBP-150NBW

Cabinet



## Key Features

- Operating Temperature: -40°C~+65°C (-40°F~+149°F) / 0~100% RH (condensing)
- Material: PC (Polycarbonate), Aluminum
- Dimensions : 360x420x163.1mm
- Weight : 3,960g
- Color : White
- Max. load: 15kg
- Certification: IP66, IK10, NEMA 4X

# SBP-150NBW

Cabinet



## Specifications

### Environmental

Operating Temperature / Humidity -40°C~+65°C (-40°F~+149°F) / 0~100% RH (condensing)  
Humidity control /w Air vent

Storage Temperature / Humidity -50°C~+65°C (-58°F~+149°F) / 0~95% RH

Certification IP66, IK10, NEMA 4X

### Mechanical

Color White

Material PC(Polycarbonate), Aluminum

RAL code RAL9003

Product dimensions / weight 360x420x163.1mm / 3,960g

Mount Screw size TR20, T30

Max. load 15kg

Conduit hole 12.7mm(1/2" )(M20, 2pcs) / 19.1mm(3/4" )(M25, 3pcs)

Supported products  
 - Installation Solution : SBP-250WMW, SBP-156WMW, SBP-400WMW, SBP-150PMW  
 - Camera : XND-C6083RV, PNV-A9081R, XNO-6083R, QNV-C8083R  
 ※ For further compatible models, please visit our website or use Toolbox