



Product Code

F14721

WIT 7" MONITOR POE WHITE MEET

Reference

14721

EAN

8424299147215

Description.

Description

WIT is a monitor with a 7" or 10" capacitive screen. WIT's graphical interface creates a truly intuitive user experience thanks to its focus on residential intercom.

CHARACTERISTICS

- Capacitive screen (7" / 10")
- Two-way hands-free communication
- High definition color TFT.
- Different ringtones based on origin
- Remote Firmware Update
- Android based
- Available in 10 languages (Spanish, English, German, Polish, Russian, Hebrew, Turkish, Chinese, Portuguese, French)
- 7 integrated alarm zones + sabotage.
- Reset and restore to factory parameters remotely.
- Doorbell with connection to CCTV IP camera
- Viewing IP CCTV cameras (up to 8)
- Simultaneous display of auxiliary IP CCTV camera and opening of auxiliary relay during conversation (up to 4)
- Activation of monitor relays (up to 8 using relay module Ref. 1616)
- Integration with home automation through Apps (in 7" and 10")
- Automatic and manual image capture
- Elevator control with feedback

Technical Details

System:

- CPU: Quad-core
- FLASH: 4GB
- SDRAM: 1024 MB

Screen:

- 7 and 10 inch format
- Capacitive touch screen
- Format: 16:9
- Resolution: 1024x600
- Brightness: 7" 200cd/m²; 10" 220cd/m²
- Contrast: 7" 400/1; 10" 450/1
- View Angle: 7" 160° Horizontal, 130° vertical; 10" 120° Horizontal, 110° Vertical

Audio/Video Features:

- G.711 audio codec
- H.264 video codec
- RTSP compatible for CCTV IP cameras
- Audio level adjustable on conversation and mute
- Hands-free operation
- Private communication
- Selectable call melodies based on call origin

Power Consumption:

- On standby: 200 mA (7") / 210 mA (10")
- Conversation: 500 mA (7") / 600 mA (10")

Working voltage:

- PoE
- 12 Vdc

Connectivity:

- 1 x Ethernet RJ-45 (WIT 7")
- 2 x Ethernet RJ-45 (WIT 10") for building and apartment network isolation.
- Doorbell input (1 alarm zone input)
- Panic button input (1 alarm zone input)
- Built in web server for configuration and remote management

Working Environment:

- Temperature: -10 oC ... +55 oC
- Humidity: 20 – 85% (Non-condensing)
- IP: 30

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
130 X 210 X 20	0.65	6,8x31x21,5	MEET

Manuals

- 970203Eb_Manual_instalador_Monitor_MIO_WIT_V11_20.pdf
- 970203Ib_Manual_instalador_Monitor_MIO_WIT_V11_20.pdf
- 970203Pb_Manual_instalador_Monitor_MIO_WIT_V02_24.pdf
- 970295_Guia_Rap_Inst_Monitor_WIT_V07_23.pdf

Declaration of conformity

- DOCF14721EN.pdf

Accessories

F95411

NEO/WIT MONITOR
CONNECTOR MEET